



Waterproof Zippered Pet Hammock



Installation and Washing Instructions

Thank you for purchasing the Waterproof Zippered Car Hammock. Your four legged best friends will enjoy your hammock, and your backseat will remain clean and protected for years to come. Installing, and removing, the hammock is quick and easy. The Waterproof Zippered Pet Hammock installs over the backseat of your vehicle and requires front and back seat head restraint posts to install.

Your hammock is completely reversible. One side is a durable, but soft and comfortable, microfiber upholstery grade fabric. The reverse side is a heavy duty Berber® fleece. You need to decide which side you, and your dog, will sit on.

The zipper allows you to easily convert the hammock to a seat cover - allowing people to sit in the backseat.



Step 1:

Remove the hammock from the plastic bag. Put the side of the hammock that you want to sit on facing up. Position the hammock on the back seat so the zipper will go against the back of the front seats (as shown in the photo).

Step 2:

Locate the two side release buckles that are on the top edge of the hammock above the zipper. If necessary, raise the driver and passenger head restraints so you can get to the head restraint posts underneath. Undo the two side release buckles. Loop the webbing around the front seat head restraint posts. Reattach the two ends of the side release buckles.

Step 3:

The top of the hammock may hang down too far from the head restraint posts. Adjust the webbing straps that go around the head restraint posts to your desired tension. Loosening, or tightening, the webbing straps also adjusts the height of the hammock between the two front seats. Some people prefer to keep the Hammock relatively tight between the two front seats to create a more substantial barrier between the front and back seats.

**If you had a great experience with your new Waterproof Zippered Pet Hammock please tell your friends. If you didn't, please tell us at:
info@floppyearsdesign.com**